

With three grades to choose from, Printronix Auto ID's comprehensive line of receipt rolls ensure a perfect match for your mobile receipt application. Designed to maximize the output and efficiency of Printronix Auto ID M4L2 mobile printers, Genuine Printronix Auto ID supplies will provide the most cost-effective, no-hassle solution available.



**Applications**

- Inventory Management
- Process Compliance
- Direct Store Delivery
- Cross-Dock Operations
- Fleet Management
- Field Service
- Electronic Citations / Parking Violations
- Ticketing Operations
- Linebusting
- Product Picking and Shipping

STANDARD	Caliper (mils/μm)	Basis Weight
Standard sensitivity with good imaging characteristics. A general purpose, economy grade providing optimum roll length for high yield and maximum duty-cycle efficiency. 7-year image life when stored under proper conditions.	<b>mils:</b> 2.09 ± 0.20 <b>microns:</b> 53 ± 5	<b>17 x 22—500 (lbs):</b> 12.2 ± 1.1 <b>g/m²:</b> 46 ± 4
PREMIUM		
Standard sensitivity with good imaging characteristics for text, barcodes and graphics. Provides all the benefits of our Standard grade product but with enhanced image stability and phenol-free chemistry. 7-year image life when stored under proper conditions.	<b>mils:</b> 2.09 ± 0.20 <b>microns:</b> 53 ± 5	<b>17 x 22—500 (lbs):</b> 12.2 ± 1.1 <b>g/m²:</b> 46 ± 4
PREMIUM DURABLE		
Top-coated for excellent environmental resistance. High sensitivity for dark, crisp images and made with a heavier base weight material for increased durability and a premium feel. Enhanced image stability and phenol-free chemistry. 7-year image life when stored under proper conditions.	<b>mils:</b> 3.3 ± 0.1 <b>microns:</b> 84 ± 5	<b>17 x 22—500 (lbs):</b> 21.7 ± 1.3 <b>g/m²:</b> 82 ± 5

\*Once thermal paper has been fully imaged on the recommended equipment, it is expected that the image will remain legible for the indicated time period, assuming the documents are properly stored with compatible materials under normal filing conditions, with a relative humidity between 45 percent and 65 percent, as well as a temperature below 77°F (25°C).

PART #	MATERIAL GRADE	DESCRIPTION	ROLLS/CTN
P150169-001	Standard	M4L2, 111mm X 62m, Receipt Roll	40
P150170-001	Premium	M4L2, 111mm X 62m, Receipt Roll	40
P150171-001	Premium Durable	M4L2, 111mm X 38m, Receipt Roll	40